

Data sheet for three-phase Squirrel-Cage-Motors



Type: 1TZ9 C 180M-4
L23+L25

Motor type: 1CV1182B

Customer :

Order no.:

Remarks :

Date :

Our order :

Item nr. :

U	Δ / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _A /I _N	T _A /T _N	T _B /T _N	
400	Δ	50	18.50	- / -	35.00	1468	120.0	89.3	90.2	90.2	0.85	0.82	0.73	7.3	2.2	3.1	IE1
690	Y	50	18.50	- / -	20.50	1468	120.0	89.3	90.2	90.2	0.85	0.82	0.73	7.3	2.2	3.1	IE1
460	Δ	60	21.30	- / -	34.50	1768	115.0	91.0	91.9	91.8	0.85	0.82	0.74	7.6	2.2	3.2	IE1
IM B35 / IM 2001			FS 180 M		170 kg	IP55	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								

Mechanical data		
Sound pressure level 50Hz/60Hz (load)	63 dB(A) ¹⁾	65 dB(A) ¹⁾
Moment of inertia	0.13 kg m²	
Bearing DE NDE	6310 C3	6310 C3
Relubrication interval/quantity	10 g 10 g 8000 h	
Lubricants	Esso Unirex N3	
Regreasing device	Yes	
Grease nipple	M10x1 DIN 3404 A	
Type of bearing	Locating bearing NDE	
Condensate drainage holes	Yes (standard)	
External earthing terminal	Yes (standard)	
Vibration severity grade	A	
Insulation	155(F)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	cast iron	
Data of anti condensation heating	-/-	
Coating (paint finish)	Standard paint finish C2	
Color, paint shade	RAL7030	
Motor protection	(A) without (Standard)	
Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box	
Terminal box position	top
Material of terminal box	cast iron
Type of terminal box	TB1 J01
Contact screw thread	M5
Max. cross-sectional area	16.0 mm²
Cable diameter from ... to ...	19.0 mm - 28.0 mm
Cable entry	2xM40x1,5
Cable gland	2 plugs

Special design (2)	
L23	Regreasing system
L25	Double sides reinforced bearings for DE and NDE, Type 63

Environmental conditions	
Ambient temperature	-20 °C - +45 °C
Altitude above sea level	1000 m

Notes	
I _A /I _N = locked rotor current / current nominal	M _K /M _N = break down torque / nominal torque
M _A /M _N = locked rotor torque / torque nominal	1) Value is valid only for DOL operation with motor design IC411