



Product Specifications

VIBOCONTROL 6000 (VC-6000) Monitoring System Power Supply Module – PS-615

The VC-6000 Monitoring System hardware is used for both stand-alone machine protection and condition monitoring using the Compass 6000 monitoring software modules and database. The VC-6000 offers various standard monitoring modules, power supply modules and communication modules. These Product Specification describes the PS-615.

The PS-615 Power Supply Module provides power to a RC-600 rack for SM-610 Monitoring Modules, sensors and CI-6xx Communication Interface Modules.

Applications

- Can be used single or connected in parallel as a double or triple redundant power supply.
- Can be used in both internal RC-600 rack (PS-615/0) and external RC-610 power supply rack (PS-615/1) configurations.

Features

- Provides independent AC and DC input.
- Secured against reversed polarity of the input voltage and short circuits of the output voltage.
- Integrated protection against over-heating and over-loading.
- 1x green LED for each output voltage and "Power OK" signal connected to the SM-610 Monitoring Modules.
- **UL certified**



Product Specifications - VC-6000 Power Supply Module – PS-610

Technical Specifications

The PS-615 is a module that mounts into the RC-600 and/or RC-610 rack.

Input

AC supply voltage 100 – 240V~ ±10%
..... 50 – 60 Hz ±5%
DC supply voltage..... 24 – 48V= ±10%

Max. power consumption..... 130 VA

Output

Voltage monitoring and current limiting against overload.

Voltage:

.....+6.5VDC (±5%), max. 6A
.....27VDC (±2%), max. 2.5A

Power-Failure Bridging Time

Fully-equipped RC-600 rack:

1x 230V~..... 50 ms
1x 24Vdc..... 3 ms
1x 48Vdc..... 5 ms

Mechanical

PS-615/0 (for mounting into the RC-600 rack):

Width..... 71 mm
Height 132.5 mm
Depth 295 mm

PS-615/1 (for mounting into the RC-610 rack):

Width..... 71 mm
Height 132.5 mm
Depth 232 mm

Weight..... approx. 1.8kg

Environmental

Operating Temperature Range..... 0 to +65°C
with air convection ≥ 1m/s

Storage Temperature Range -40 to +85°C

Operating and Storage Humidity95% RH non-cond.

Accessories

Scope of Delivery for PS-615/0

(for mounting into the RC-600 rack):

1x PS-615 Power Supply Module
1x AC-4603 Mounting adapter
1x AC-4602/04 Blind panel 3HE 4TE
1x DC Power plug with cable, 5m long, open ends
1x AC Power plug with cable, 5m long, open ends

Scope of Delivery for PS-615/1

(for mounting into the RC-610 rack):

1x PS-615 Power Supply Module
1x Output plug
1x DC power plug with cable, 5m long, open ends
1x AC power plug with cable, 5m long, open ends

Brüel & Kjær Vibro reserves the right to change specifications without notice

Brüel & Kjær Vibro A/S
2850 Nærum – Denmark
Tel.: +45 7741 2500
Fax: +45 4580 2937
E-mail: info@bkvibro.com

Brüel & Kjær Vibro GmbH
64293 Darmstadt – Germany
Tel.: +49 (0) 6151 428 1100
Fax: +49 (0) 6151 428 1200
E-mail: info@bkvibro.de