

Part Number: ZVA2 4.4 D EK043black EK044black -



© ELAFLEX, Hamburg / Germany

<https://nozzleconfigurator.elaflex.fr/ZVA SLIMLINE 2/1463/20760/23913/SW/20607/WITHOUT PSB/WITHOUT PSB/NOPROP/23775/24678/20819/20894/21300/20907/000/20913/21198/Product19.html>

Nozzle Type	ZVA Slimline 2 for petrol stations Automatic nozzle Max. flowrate 80 l/min. Suitable for gasoline (also with ethanol content up to E 85), diesel, fuel oil, biodiesel. Not suitable for viscous oils. Certificate: Meets EN 13012. Fulfills the requirements of safety and weight and measures. ATEX (Ex II 1 G Ex h IIA) certificate no.: TPS 19 ATEX 103415 0002 U. TÜV approval P-TÜ7-01930.
Body	ZVA Slimline 2 (Standard) Standard
Guard	EG 281.4 Guard No. 4
Connection	Swivel Easy-rotating swivel.
Swivel	EA 075.4 $\frac{3}{4}$ " BSP female
Pump Safety Break	Without
Pump Safety Break	Without
PSB Propeller	-
Break Sleeve	Without break sleeve Without
Spout	ER 042.1 Standard spout OD 25 mm, for Diesel / Biodiesel.
Latching	Without latch Pin Deadman function Without hold-open function.
DSA	Without DSA (Standard)

Special Type	Standard vacuum cap Standard Temperature range -20° C up to +55° C With seals and diaphragm for operating in moderate climate regions to -20° C.
Scuffguard	EK 044 black Scuffguard black
Badge	-
Product Sleeve / Splashguard	EK 043 black Product Sleeve black
Strainer	EK 172 Standard strainer Strainer 400 µm (40 mesh), white.

PDF Documents

-  Page 517-520 (ZVA Slimline 2 for petrol stations)
-  ATEX Certification no. TPS 19 ATEX 103415 0002 U (ZVA Slimline 2 for petrol stations)
-  TÜV approval P-TÜ7-01930 (ZVA Slimline 2 for petrol stations)

Contact:

ELAFLEX France SARL
Aktipark
50 Rue des Chardonnerets,
Lot N° 3
F-93290 Tremblay en France
Phone No.: +33 (0) 1 41 84 06 22
Internet: www.elaflex.fr