

Data sheet

Ref. no.	Datenblätter IE3 2Pol	Sales order	SODK-253166
Item no. / Configuration	01 / 3102112-4.00-010201-M-051669	Our reference	Henning Krey
Description	HMA3 112M-2 400/690V 50Hz 4kW	Date	06-07-2026

General data	
Standard series	IEC 60034
Type	HMA3 112M-2
Design	400 VD / 690 VY 50 Hz + 480 VD / 830 VY 60 Hz
Direction of rotation	CW
Installation max. altitude (m)	1.000
Poles	2

Motor protection	
Winding temp. detector	No
Temp. detector type	None
Bearing detector	No
Winding PTC main	PTC 3 x 155°C
Winding PTC secondary	None
Space heater	None
Terminal board thread	M5
Electrical insulation	Standard (1350 V @ 0.8 µs)
Tropical insulation	No
SPM	N/A
External grounding	No
Drain hole	Yes
Rain cap	No

Classification	
Class society	
Materials approval	None
Ex. code	No
Industrial certification	CE, UKCA


Mechanical data	
Frame / Shaft height	IEC 112
Type of construction	B3
Cooling method	IC411
Protection class	IP55
Temp. insulation class	F
Frame material	Aluminum
Keyway	Closed
Balancing	Half key
IEC vibration class	A
Weight (kg)	34.1
Bearing (DE)	6306 2Z / C3 / DGBB
Bearing (NDE)	6306 2Z / C3 / DGBB
Fixed bearing	DE
Moment of inertia (kg×m²)	0.007
Painting (color)	RAL 9005
Corrosion protection	C3L
Main terminal box pos.	DE top
Main cable entries	Blind cap 2xM20x1.5
Main cable direction	Right from DE
Main cable material	Plastic
Aux. cable entries	Blind cap 1xM20x1.5
Aux. cable direction	NDE
Aux. cable material	Plastic

Winding operation variants						
Rated power (kW)	4	4	4.8			
Frequency (Hz)	50	60	60			
Connection	D/Y	D/Y	D/Y			
Voltage (V)	400 / 690	480 / 830	440 / 762			
Full load current (A)	7.1 / 4.1	6.03 / 3.49	7.3 / 4.2			
No load current (A)	2.11	2.11	1.79			
Speed (rpm)	2915	3498	3498			
Power factor 100/75/50 (%)	0.92 / 0.91 / 0.9	0.92 / 0.89 / 0.82	0.99 / 0.96 / 0.93			
Efficiency 100/75/50 (%)	88.1 / 88.9 / 87.9	88.5 / 87.3 / 86.4	88.5 / 88.1 / 87.1			
Efficiency class	IE3	IE3	IE2			
Full load torque (Nm)	13.1	10.9	13.1			
Tst/Tn	2.61	3.13	2.35			
Tmax/Tn	3	3.6	2.67			
Ist/In	8.72	10.3	8.72			
Temp. rise class	B	B	B			
Duty	S1	S1	S1			
Sound pressure level (dBA)	67	72	67			
Min. ambient temp. (°C)	-20°C	-20°C	-20°C			
Max. ambient temp. (°C)	40°C	40°C	45°C			

Data are not binding. Hoyer reserves the right to implement changes without notice. The extent of data are not equivalent to nameplate on the motors.

Data sheet

Ref. no.	Datenblätter IE3 2Pol	Sales order	SODK-253166
Item no. / Configuration	01 / 3102112-4.00-010201-M-051669	Our reference	Henning Krey
Description	HMA3 112M-2 400/690V 50Hz 4kW	Date	06-07-2026



A 190.00	AA 45.00	AB 222.00	AC 219.00	AD 168.00	B 140.00	BB 180.00	C 70.00	D 28.00	DB 10.00	E 60.00	EB 50.00	EG 28.00	F 8.00	G 24.00	GD 7.00
H 112.00	HA 13.00	HB 145.00	HD 280.00	K 18.00	L 390.00	LB 330.00	TB 120.00	TL 120.00							