



SCHEMA TECNICA BOBINA 8000BH/J5IV

DESCRIZIONE	
BOBINA 30mm CON CONNESSIONI A NORMA DIN43650-A	
CARATTERISTICHE	
TENSIONE	220/230 Vac
FREQUENZA	50 Hz
POTENZA	15 VA (a freddo)
TIPO DI SERVIZIO	Continuo (ED100%)
CLASSE DI ISOLAMENTO ELETTRICO	I
CLASSE DI TEMPERATURA	H
CLASSE DI PROTEZIONE (senza connettore DIN43650-A)	IP00
CLASSE DI PROTEZIONE (con connettore DIN43650-A)	IP65
OMOLOGAZIONI	VDE

Data:	28/04/10
Rev.	00
Compilato da:	Massarotto



DATA SHEET FOR COIL 8000BH/J5IV

DESCRIZIONE	
30mm COIL WITH CONNECTION TERMINALS IN COMPLIANCE WITH DIN 43650-A	
CARATTERISTICHE	
POWER SUPPLY	220/230 Vac
FREQUENCY	50 Hz
POWER	15 VA (at room temperature)
TYPE OF SERVICE	Continuos (ED100%)
ELECTRICAL INSULATION CLASS	I
TEMPERATURE CLASS	H
PROTECTION CLASS (without connector DIN43650-B)	IP00
PROTECTION CLASS (with connector DIN43650-B)	IP65
APPROVAL	VDE

Date:	28/04/10
Rev.	00
Filled out by:	Massarotto

All technical information provided are simply indicative.

They are the result of laboratory tests, which have to be considered a restricted example compared to the case history relating to the possible use of these products.

On the basis of these considerations, all these technical information are liable to be considerably changed depending on the different conditions of use or assembly of the product onto the final equipment.

Therefore, we suggest the users should always subject the product to preliminary tests by simulating its future and real conditions of use.