





	Model	Ø	H (A Type Diaphragm Valves) - Size in mm										
			015	020	025	032	040	050	065	080	100	125	150
Fail Safe Spring to Close	ES61	169	408	413	423		435	461					
	ES62	260			462		476	501	501	503			
	ES63	316						700	729	732	756		
	ES64	425								784	800	828	895
	ES65	549									1031	1059	1125
Fail Safe Spring to Open	ES68	169	378	383	393		406	432					
	ES69	260			497		511	537	536	538			
	ES70	316						773	783	786	810		
	ES71	425								763	786	813	881
	ES72	549									879	907	974
Double Acting	ES54	169	155	160	170		183	209					
	ES55	260			222		235	246	259	271			
	ES56	316						306	315	318	357		
	ES57	425								336	363	378	444
	ES58	549									382	410	479

	Model	Ø	H (KB Type Diaphragm Valves) - Size in mm										
			015	020	025	032	040	050	065	080	100	125	150
Fail Safe Spring to Close	ES61	169			480		480						
	ES62	260			520		521	518	547				
	ES63	316						740	765	797	827		
	ES64	425								841	871	847	962
	ES65	549									1102	1078	1193
Fail Safe Spring to Open	ES68	169			450		450						
	ES69	260			556		557	555	582				
	ES70	316						794	819	850	881		
	ES71	425								827	857	833	948
	ES72	549									950	926	1041
Double Acting	ES54	169			227		227						
	ES55	260			280		281	280	307				
	ES56	316						326	351	382	413		
	ES57	425								400	430	406	521
	ES58	549									453	429	544

Note

All dimensions are based on unlined bodies and bareshaft actuators. Add on handwheel dimensions are below.

Actuator	Add-on
68 / 69 / 70	+ 14mm
61 / 62 / 63	+ 14mm
71 / 64	+ 18mm