

CODE	MODEL	Nominal volume (litres)	H (mm)	øD (mm)	E (mm)	ØC	Precharge pressure ± 20% (bar)	Max operating pressure (bar)
11000024J2	IN LINE NO BASE	25	485	270		G1	2	16
1100010079	VERT. MODEL	100	910	450	153	G1	2	16
11000200AE	VERT. MODEL	200	1235	550	210	G1 ½	2	16
1100030098	VERT. MODEL	300	1365	630	188	G1 ½	2	16
1100050083*	VERT. MODEL	500	1470	750	143	G1 ½	2	16

Max operating pressure: 16 bar
System temperature: -10 / +99 °C
Factory precharge: 2,0 +/-20% bar
Nominal volume: SEE TABLE
Colour: RAL3002 / *RED

500(L) VERT.

100÷300(L) VERT.

25(L) IN LINE

1	UPPER SHELL	1	CARBON STEEL
2	LOWER SHELL	1	CARBON STEEL
3	MEMBRANE	1	SYNTHETIC RUBBER
4	PRECHARGE VALVE	1	BRASS
5	THREADED NOZZLE	1	CARBON STEEL
6	SELF-ADHESIVE LABEL	1	-
7	CLOSURE FLANGE	1	CARBON STEEL
8	LEG	3	CARBON STEEL
9			
Pos.	Denomination	Q.ty	Material

Revisioni		
Rev.	Descrizione	Data
01	Redesigned with S.W.	23/05/2017
02	Removed pump bracket	28/04/2022

GITRAL®
ZI DE BOURNAT F63190 ORLEAT

DENOMINATION
**G-HP 25÷500L 16BAR
CE**

DRAWING N°		SCALE	MATERIAL
HP		1:20	SEE TABLE
DRAWN	DATE	SIGNATURE	CODE SEE TABLE
CHECKED	DATE	SIGNATURE	
APPROVED	DATE	SIGNATURE	
CHERVIN P.	28/04/2022		

Dimensions in mm

This drawing is the property of company GITRAL S. A. All rights reserved.

A3

All dimension tolerances not indicated are ± 2% for lenght and ± 3mm for diameter