# BKPA-VGA 101KF

(BKPA-VGA 101K-FK)

**Light duty fixed castor, with top plate fitting, wheel, with solid rubber tyres, with synthetic rim, with synthetic thread guard**



**ID** 756996
**EAN** 4047526117382
**Customs tariff number** 87169090

Made in Germany

**Bracket:** BKPA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Wheel:** VGA series

- tyre: high-quality solid rubber, hardness 80 Shore A, colour dark grey, non-marking, non-staining
- rim: high-quality polypropylene, injection-moulded rim, colour silver grey

**Other features:**

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C

**Technical specifications:**

| | |
|---|---|
| Wheel Ø (D) (mm / inches) | 100 / 4 |
| Wheel width (T2) (mm / inches) | 32 / 1 ¼ |
| Load capacity at 4 km/h (kg / lbs) | 120 / 265 |
| Bearing type | ball bearing (C) |
| Total height (H) (mm / inches) | 136 / 5 ⅜ |
| Plate dimension (A x B) (mm / inches) | 90 x 66 / 3 ⁹⁄₁₆ x 2 ⅝ |
| Bolt hole spacing (a x b) (mm / inches) | 75 x 45 / 61 x 51 / 2 ³¹⁄₃₂ x 1 ²⁵⁄₃₂ / 2 ¹³⁄₃₂ x 2 ¹⁄₁₆ |
| Bolt hole Ø (mm / inches) | 8.5 / ⁵⁄₁₆ |
| Temperature resistance min. (°C / °F) | -20 / -5 |
| Temperature resistance max. (°C / °F) | 60 / 140 |
| Tread and tyre hardness | 80 Shore A |
| Unit weight (kg / lbs) | 0.5 / 1.1 |
| Non-marking | ✓ |
| Electrically conductive | - |
| ESD | - |
| Antistatic | - |
| Corrosion-resistant | - |
| Heat-resistant | - |
| Non-staining | ✓ |
| Suitable for autoclaves | - |
| Suitable for machine washing | - |

**Tread & tyre hardness**
80 Shore A

**Floor preservation / smooth operation**
very good

**Rolling resistance**
good

**Wear resistance**
satisfactory

