Robertshaw ROBERTSHAW INDUSTRIAL PRODUCTS DIVISION	**PRICE LIST** **Vibraswitch® Detector Model EURO 366**	Price List: **PL EURO366** Sales Manual Section: **Vibration Detection 140** Issue Date: **Sep 1, 2015** Supersedes Issue Date: **Oct 1, 2014** Discount Code: **L**

ORDERING INFORMATION AND MODEL NUMBER CODING

EURO 366 - A 8 - H 2 - A - F X - X

- **Key Model Number**
- **Table 1 – Switch Contacts**
- **Table 2 – Remote Reset**
- **Table 3 – Enclosure Type**
- **Table 4 – Enclosure Finish**
- **Table 5 – Switch Rating**
- **Table 6 – Enclosure Inlet**
- **Table 7 – Enclosure Outlet**
- **Table 8 – Space Heater**

STANDARD MODEL: EURO 366 - A 8 - H 2 - A - F X - X

KEY MODEL NUMBER

MODEL NO.	DESCRIPTION	BASE
EURO 366	Vibraswitch® CE & ATEX Certified Flameproof (Explosion proof) Ex d IIB/IIC T6 tD A21 IP66 T85°C (**CAST ALUMINUM**)	
EURO 366G	Vibraswitch® CE & ATEX Certified Flameproof (Explosion proof) Ex d IIB/IIC T6 tD A21 IP66 T85°C (**CAST IRON**)	

Table 1 – SWITCH CONTACTS

DESIGNATION	DESCRIPTION	ADD TO BASE
A	SPDT - single pole double throw load contacts Use with Table 5, Designation A only.	No Charge
D	DPDT - 2 gang mounted SPDT load switches Use with Table 5, Designations E or H only.	

Table 2 – REMOTE RESET

DESIGNATION	DESCRIPTION	ADD TO BASE
0	No reset coil	
2	24 VDC, 0.5 amp	No charge
4	48 VDC, 0.2 amp	No charge
7	120 VDC, 0.14 amp	No charge
8	120 VAC, 0.3 amp	No charge
9	240 VAC, 0.3 amp	

Table 3 – ENCLOSURE TYPE

DESIGNATION	DESCRIPTION	ADD TO BASE
H or W*	CS-INVR (with manual reset) T cable 105° C (-40 to +60° C)	No charge

* For EURO366G Model use W

Table 4 – ENCLOSURE FINISH

DESIGNATION	DESCRIPTION	ADD TO BASE
1*	Unpainted (Sand Blasted) for EURO366	
2	Standard Paint- EURO366 (dark green) EURO366G (Orange)	No Charge
3*	Gray (Powder Coated) for EURO366G	CF

* Has Extended Lead Time

Table 5 – SWITCH RATING

DESIGNATION	DESCRIPTION	ADD TO BASE
A	SPDT 7 amp max. - May only be used with Table 1, Designation A	No Charge
E	DPDT 5 amp max. - May only be used with Table 1, Designation D	No Charge
H	DPDT 0.1 amp max., gold plated contacts for low voltage/current applications May only be used with Table 1, Designation D	

Table 6 – ENCLOSURE INLET

DESIGNATION	DESCRIPTION	ADD TO BASE
F	3/4" UNI Plug ***Omit when ordering EURO366G***	No Charge

Table 7 – ENCLOSURE OUTLET

DESIGNATION	DESCRIPTION	ADD TO BASE
X	3/4" UNI 6125 threaded entry	No Charge

Table 8 – SPACE HEATER

DESIGNATION	DESCRIPTION	ADD TO BASE
F	24 VDC, 2 watt - with SPDT switch (when used with Table 1, Designation A)	
	24 VDC, 2 watt - with DPDT switch (when used with Table 1, Designation D)	
G	48 VDC, 2 watt - with SPDT switch (when used with Table 1, Designation A)	
	48 VDC, 2 watt - with DPDT switch (when used with Table 1, Designation D)	
H	120 VAC, 2 watt - with SPDT switch (when used with Table 1, Designation A)	
	120 VAC, 2 watt - with DPDT switch (when used with Table 1, Designation D)	
L	120 VDC, 2 watt - with SPDT switch (when used with Table 1, Designation A)	
	120 VDC, 2 watt - with DPDT switch (when used with Table 1, Designation D)	
M	240 VAC, 2 watt - with SPDT switch (when used with Table 1, Designation A)	
	240 VAC, 2 watt - with DPDT switch (when used with Table 1, Designation D)	
X	No space heater	No Charge

ACCESSORIES

Part Number	DESCRIPTION	ADD TO BASE
40274-A1	¾" – ½" NPT Adaptor	
40274-B1	¾ - M20 Adaptor	