

K50FLGRY2P
LED Indicator – Beacon



Features

- LED all-round visible
- Flat mounting
- Individually controllable
- Protection classes IP67/IP69K
- Multicolor: Green (COL 1) / Red (COL 2) / Yellow (COL 3)
- Cable, 2 m
- Operating voltage 18…30 VDC
- Flashing or alternating
- Flashing function adjustable via terminal programming

Wiring diagram



Technical data

Type	K50FLGRY2P
ID	3083440
Signal and display data	
Purpose	LED indicator light
Function	Spotlight
Light type	Green Red Yellow
Dimmable	no
Features of color 1	Green, Miscellaneous
Features of color 2	Red
Features of color 3	Yellow
Special features	Wash down
Electrical data	
Operating voltage	18…30 VDC
DC rated operational current	≤ 50 mA
Max. current consumption per color	50 mA
Input type	PNP
Response time typical	< 250 ms
Mechanical data	
Cascadable	No
Design	Dome, K50F
Dimensions	50 x 76 x 44.6 mm
Housing material	Plastic, PC, Black
Window material	Polycarbonate, diffuse
Electrical connection	Cable, 2 m, PVC
Number of cores	4

Functional principle

The LED display is suitable for industrial use thanks to its rugged design in protection class IP67. Depending on the pin assignment, one of the three colors lights either steady or flashes during the period of one PNP input signal. The "2" in the type code indicates the flashing function of the LED. For example: when connecting the brown and the black wire to 24 VDC, the LED starts flashing red. You find a more detailed description of the terminal programming in the instruction leaflet delivered with the item. Alternate flashing of all colors is also possible.
The wiring diagram shows the PNP input configuration. An instruction leaflet with detailed information about the connection is included with the devices.


K50FLGRY2P | 19-01-2022 06-37 | Technical modifications reserved

Technical data

Ambient temperature	-40…+50 °C
Relative humidity	0…95 %
Protection class	IP67 IP69
Tests/approvals	
Approvals	CE


Accessories

SMB30A	3032723



Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread

SMB30SC	3052521



Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable

K50FLGRY2P | 19-01-2022 06-37 | Technical modifications reserved